

FRONTIER RIG 16 | RIG INVENTORY

DRAWWORKS: 1,500 Hp, Continental Emsco C1 with Baylor 6032 Electric Brake

MOBILITY: Uni-Directional Skid System up to 90'

MAST: DSI 142 FT - 750,000 LB Static Hook Load

SUBSTRUCTURE: DSI 31' Floor Height Box on Box – 400,000 Setback

GENERATORS: (3) Caterpillar 3512C Diesel Engines w/ 1,365 KW Generators

Control House: 1600A 4x4 Bay M&I Electric with Dynamic Braking and PLC Failover System

MUD PUMPS: (3) 1600 HP 12P160 p/b (2) 1000 HP High Torque GE 752 Motors Each, 7,500 PSI

Fluid Ends with P-Quip Liner and Piston Retention System

TOP DRIVE: Canrig 1250AC 500 Ton Top Drive with 7,500 PSI Fluid System and Rig Floor

Mounted TDSU

CATWALK: Canrig PC-3000 Hydraulic Catwalk with Walking Package, Hydraulic V-Door,

Wireless Control

HANDLING TOOL: National ST-80C

ROTARY TABLE: National 275, 27.5" Table

BOP: 13-5/8" 5,000 PSI Double Ram with 13-5/8" 5,000 PSI Annular

MUD SYSTEM: 1,100 BBL with 6×8 Mixing Pumps and 10 HP Agitators, Desander, Desilter, 48"

Mud/Gas Separator

SHALE SHAKERS: (3) MI SWACO Linear Motion

CHOKE MANIFOLD: 4" 5,000 PSI Skid Mounted

FUEL TANK: 12,000 Gallon Dual Wall Fuel Tank w/ integrated redundant fuel pumps

WATER TANK: 500 BBL

DOG HOUSE: 10' x 8' x 45' DS, 10' x 8' x 22' ODS

TRAVELING BLOCK: National 500 Ton with 50" Sheaves for 1-3/8" Drilling Line

MISCELLANEOUS: Parts House, Pipe Racks, Misc. Handling Tools

LIGHTING SYSTEM: 100% LED Class I DIV I, Class I DIV II Area, Spot and Flood Fixtures

POWER UNIT: Centralized HPU with Redundant Motors/Pumps and Temp/Level Protection

4801 Richmond Sq., Oklahoma City, OK 73118 | Phone 405-745-7700 | Fax 405-745-6700